



PRODUCT DATA



300RE Asphalt Remover (Formerly BEAN•E•D00® Asphalt Cleaner)

Taking off difficult, high-oil type asphalts is a snap with **300RE**. Effectively removes modified asphalts, polymers, top coating, coal tar, and tac-coatings, keeping equipment and tools clean and free of build-up. Not only is **300RE** a great cleaner, it's a great protectant as well. Pre-applying to metal surfaces before using helps to keep asphalt from bonding tightly to the surface, making cleaning easier than ever!

Coverage:

Average coverage is 100-200 sq ft per gallon.

Application:

Spray undiluted **300RE** directly on asphalt build-up. Let sit until build-up has softened. Thicker build-ups may require multiple applications or longer dwell times.

Clean Up:

Spray clean with pressured hose or power washer.

Usage Tips from the Pros:

- Pre-apply **300RE** to clean metal surfaces to help prevent asphalt from bonding.
- For large machinery or application areas, use a pump-up sprayer with chemical resistant seals.
- Build-ups of more than 1/2" thick may require multiple applications.

Biodegradable:

Meets or exceeds ASTM standards

Precautions:

300RE is designed to break down asphalt based surfaces. Protect surfaces not intended for **300RE**.

Warnings:

May cause mild skin irritation. May cause eye irritation. May be harmful if swallowed. Keep out of reach of children.

Flash Point:

Above 425°F (218.33°C)

pH Level:

6.65 pH of 1/10 wt/wt solution in soft water

VOC (Volatile Organic Compounds):

2.3%, .06 lb/g, 20 g/l
California and OTC Compliant

Ingredients:

Soy Ester, Proprietary Surfactant Blend

NON-EMERGENCY

Call: 800.538.5069

www.franmar.com

CHEMICAL EMERGENCY:

Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night

USA and Canada: 800.242.9300

CCN717946 or +1 703.527.3887

(Collect Calls Accepted)



PO Box 5565
Bloomington IL 61702
Copyright 2014

Rev. 1/23/2015