

Bucket of Safe-Tie

Part #	Description
00800	Velocity Harness (01700), 5 Snappy Anchors (00710), & VLA-25' (01310)
00803	Velocity Harness (01700), 1 SP-Anchor (00460), & VLA-25' (01310)
00805	Velocity Harness (01700), 1 Temper Anchor (00455), & VLA-25' (01310)
00810	Velocity Harness (01700), 5 Snappy Anchors (00710), & VLA-50' (01320)
00813	Velocity Harness (01700), 1 SP-Anchor (00460), & VLA-50' (01320)
00815	Velocity Harness (01700), 1 Temper Anchor (00455), & VLA-50' (01320)
00830	Velocity Harness (01700), 2 Reusable Anchors (00470), & VLA-25' (01310)
00840	Velocity Harness (01700), 2 Reusable Anchors (00470), & VLA-50' (01320)

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-07, and ANSI A10.32-2012 regulations.

Custom configurations available. Contact customer service for details.

Bucket of Safe-Tie is suitable for the following applications:



Personal Fall Arrest: Bucket of Safe-Tie components may be used in combination as a complete Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6'. Applicable D-ring: Dorsal.



Restraint: Bucket of Safe-Tie components may be used in combination in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No vertical free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-310 lbs.

Materials: stainless steel, nylon, and polyester.

Always read and understand all equipment-specific instructions.

MAXIMUM 1 user per Bucket of Safe-Tie PFAS.

UPC-A Codes:

00800: 672421008004	00813: 672421008134
00803: 672421008035	00815: 672421008158
00805: 672421008059	00830: 672421008301
00810: 672421008103	00840: 672421008400

Packing Dimensions: 12"L x 12"W x 15"H
Weight: 15 lb. per unit.
Quantity: 36 per pallet, 580 lbs.



Not repairable.
Remove from service
if exposed to forces
of fall arrest.